

# Blower



## Features

- Equipped with high static pressure and low noise centrifugal fan, spring shock absorber is installed between the fan and casing
- Novel design
- PVC inner insulation
- **Wide-range in application**, it can be used as supply and exhaust fan and equipped with other ventilation systems to boost the air pressure

Series	Construction	Model	Airflow (m <sup>3</sup> /h)			E.S.P.(Pa)			Dimension (mm)			Duct size (mm)	Volt. (V)	Power (W)	Weight (Kg)
			L	M	H	L	M	H	L	W	H				
Small series	Galvanized steel sheet, round duct connection	HF-02	150	200	200	120	130	135	350	350	264	Φ144	220	10	10
		HF-03	250	300	300	130	137	140	402	372	270	Φ144	220	20	12
		HF-04	350	400	400	145	150	153	425	372	270	Φ144	220	40	14
		HF-06	500	600	600	175	180	185	452	452	270	Φ194	220	60	18
		HF-08	700	800	800	190	194	198	500	520	388	Φ242	220	180	35
		HF-10	900	1000	1000	178	182	185	500	520	388	Φ242	220	180	36
Middle series	Colored steel sheet, rectangle flange and no frame constructed	HF-16	1600			300			600	600	560	320×160	380	370	24
		HF-20	2000			320			600	600	560	320×160	380	450	30
		HF-26	2600			340			600	600	560	320×250	380	550	33
		HF-30	3000			350			600	600	560	320×250	380	550	35
		HF-40	4000			400			785	700	700	320×250	380	1500	47
		HF-50	5000			460			900	900	900	500×300	380	2200	78
		HF-60	6000			500			900	900	900	500×300	380	3000	85
Large series	Colored steel sheet, rectangle flange, frame and plate constructed	HF-75	7500			590			900	1180	1000	500×400	380	3000	96
		HF-100	10000			720			1180	1080	1080	630×400	380	5500	150
		HF-150	15000			950			1400	1020	1220	630×500	380	7500	200
		HF-200	20000			900			1500	1250	1300	630×500	380	11000	450
		HF-300	30000			810			1700	1500	1430	800×500	380	15000	680